

[illegible]

10

- 15

20

2. The method of claim 1 wherein
- said local IP address pool includes a high watermark that indicates the maximum number of IP addresses used by said network edge device;

5 reallocated to give more IP addresses to the network element associated with said
high watermark when said high watermark exceeds said high watermark limit.

15 said low watermark when said low watermark exceeds said low watermark limit.

allocating an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from a local IP address pool when said high watermark is less than said high watermark limit and said low watermark is greater than said low watermark limit.

5

5. The method of claim 1 wherein

each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said low watermark of said

10

address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be reallocated to reclaim IP addresses from the network element associated with said low watermark when said low watermark exceeds said low watermark limit.

15

6. The method of claim 3 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

said high watermark is expressed as a percentage of allocated IP addresses.

20

7. The method of claim 6 wherein said network operates according to a simple network management protocol (SNMP).

8. The method of claim 7 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

9. A method for managing Internet Protocol (IP) addresses on a data communications network, comprising:

5 allocating a plurality of local IP address pools, each of said local IP address pools associated with a different network edge device capable of accepting connection requests requiring an IP address, said network edge device having a local memory, said local memory including a local IP address pool database; receiving a communication from said network edge device, said communication
10 including an IP address usage summary; determining whether one or more of said plurality of local IP address pools should be adjusted based upon said IP address usage summary; and adjusting one or more of said plurality of local IP address pools based upon said determining.

15 10. The method of claim 9 wherein:

20 said local IP address pool includes a high watermark that indicates the maximum number of IP addresses used by said network edge device; said determining further comprises ascertaining whether said high watermark of a local address pool exceeds a high watermark limit; and said method further comprises indicating one or more IP address pools should be reallocated to give more IP addresses to the network element associated with said high watermark when said high watermark exceeds said high watermark limit.

11. The method of claim 10 wherein

each said local IP address pool further comprises a low watermark that indicates the

minimum number of IP addresses used by said network edge device;

5 said determining further comprises ascertaining whether said low watermark of a said address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be

reallocated to reclaim IP addresses from the network element associated with

said low watermark when said low watermark exceeds said low watermark limit.

10

12. The method of claim 11 wherein said reallocating further comprises:

allocating an IP address from IP addresses reclaimed from other IP address pools

when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is insufficient;

15 allocating an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from a local IP

address pool when said high watermark is less than said high watermark limit

20 and said low watermark is greater than said low watermark limit.

13. The method of claim 9 wherein

each said local IP address pool further comprises a low watermark that indicates the

minimum number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said low watermark of said address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be

5 reallocated to reclaim IP addresses from the network element associated with said low watermark when said low watermark exceeds said low watermark limit.

14. The method of claim 11 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

10 said high watermark is expressed as a percentage of allocated IP addresses.

15. The method of claim 14 wherein said network operates according to a simple network management protocol (SNMP).

16. The method of claim 15 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

17. A method for managing Internet Protocol (IP) addresses on a data communications

20 network, comprising:

receiving a communication;

allocating an available IP address from said local IP address pool if said

communication includes a connection request, said local IP address pool

associated with a different network edge device capable of accepting connection

25 requests;

determining whether said local IP address pool should be adjusted;
sending a alarm message to an IP pool manager when said IP address pool should be
adjusted; and

- 5 storing an IP address allocation when said communication includes an IP address
allocation.

18. The method of claim 17 wherein

said local IP address pool includes a high watermark that indicates the maximum

- 10 number of IP addresses used by said network edge device; and

said determining further comprises:

ascertaining whether said high watermark of a local address pool exceeds a high
watermark limit; and

indicating one or more IP address pools should be reallocated to give more IP

- 15 addresses to said network edge device when said high watermark exceeds
said high watermark limit.

19. The method of claim 18 wherein

each said local IP address pool further comprises a low watermark that indicates the

- 20 minimum number of IP addresses used by said network edge device; and

said determining further comprises:

ascertaining whether said low watermark of said address pool exceeds a low
watermark limit; and

TO: T359260

said method further comprises indicating one or more IP address pools should be reallocated to reclaim IP addresses from said network edge device when said low watermark exceeds said low watermark limit.

5

20. The method of claim 19 wherein said reallocating further comprises:

allocating an IP address from IP addresses reclaimed from other IP address pools when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is insufficient;

10

allocating an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from said local IP address pool when said high watermark is less than said high watermark limit and said low watermark is greater than said low watermark limit.

15

21. The method of claim 17 wherein

each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device; and

20

said determining further comprises:

ascertaining whether said low watermark of said local address pool exceeds a low watermark limit; and

indicating one or more IP address pools should be reallocated to reclaim IP addresses from the network element associated with said low watermark when said low watermark exceeds said low watermark limit.

5

22. The method of claim 19 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and
said high watermark is expressed as a percentage of allocated IP addresses.

10 23. The method of claim 22 wherein said network operates according to a simple network management protocol (SNMP).

24. The method of claim 23 wherein

said low watermark is stored in an expression MIB; and
15 said high watermark is stored in an expression MIB.

25. A program storage device readable by a machine, embodying a program of instructions executable by the machine to perform a method to manage Internet Protocol (IP) addresses on a data communications network, the method comprising:

20 allocating a plurality of local IP address pools, each of said local IP address pools associated with a different network edge device capable of accepting connection requests requiring an IP address, said network edge device having a local memory, said local memory including a local IP address pool database;
requesting IP address usage data from one or more of said network edge devices;
25 receiving said requested IP address usage data;

determining whether one or more of said plurality of local IP address pools should be
reallocated based upon at least said requested IP address usage data;
reallocating one or more of said plurality of local IP address pools based upon said
5 determining; and
updating one or more of said local IP address pool databases and a global IP pool
database based upon said reallocating, said global IP address pool database
including the information maintained in each said local IP address pool.

10 26. The program storage device of claim 25 wherein

said local IP address pool includes a high watermark that indicates the maximum
number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said high watermark of a
local address pool exceeds a high watermark limit; and

15 said method further comprises indicating one or more IP address pools should be
reallocated to give more IP addresses to the network element associated with said
high watermark when said high watermark exceeds said high watermark limit.

27. The program storage device of claim 26 wherein

20 each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said low watermark of said
address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be
reallocated to reclaim IP addresses from the network element associated with
said low watermark when said low watermark exceeds said low watermark limit.

5

28. The program storage device of claim 27 wherein said reallocating further comprises:

allocating an IP address from IP addresses reclaimed from other IP address pools
when said high watermark exceeds said high watermark limit and when the
number of unallocated IP addresses is insufficient;

10

allocating an IP addresses from unallocated IP addresses when said high watermark
exceeds said high watermark limit and when the number of unallocated IP
addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from a local IP
address pool when said high watermark is less than said high watermark limit
and said low watermark is greater than said low watermark limit.

15

29. The program storage device of claim 25 wherein

each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device;

20

said determining further comprises ascertaining whether said low watermark of said
address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be
reallocated to reclaim IP addresses from the network element associated with
said low watermark when said low watermark exceeds said low watermark limit.

30. The program storage device of claim 27 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

5 said high watermark is expressed as a percentage of allocated IP addresses.

31. The program storage device of claim 30 wherein said network operates according to a simple network management protocol (SNMP).

10 32. The program storage device of claim 31 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

33. A program storage device readable by a machine, embodying a program of

15 instructions executable by the machine to perform a method to manage Internet Protocol (IP) addresses on a data communications network, the method comprising: allocating a plurality of local IP address pools, each of said local IP address pools

associated with a different network edge device capable of accepting connection requests requiring an IP address, said network edge device having a local

20 memory, said local memory including a local IP address pool database;

receiving a communication from said network edge device, said communication

including an IP address usage summary;

determining whether one or more of said plurality of local IP address pools should be

adjusted based upon said IP address usage summary; and

095001-01401
TOP SECRET

adjusting one or more of said plurality of local IP address pools based upon said
determining.

5 34. The program storage device of claim 33 wherein:

said local IP address pool includes a high watermark that indicates the maximum
number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said high watermark of a
local address pool exceeds a high watermark limit; and

10 said method further comprises indicating one or more IP address pools should be
reallocated to give more IP addresses to the network element associated with said
high watermark when said high watermark exceeds said high watermark limit.

35. The program storage device of claim 34 wherein

15 each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said low watermark of a said
address pool exceeds a low watermark limit; and

20 said method further comprises indicating one or more IP address pools should be
reallocated to reclaim IP addresses from the network element associated with
said low watermark when said low watermark exceeds said low watermark limit.

TO THE PUBLIC

36. The program storage device of claim 35 wherein said reallocating further comprises:

allocating an IP address from IP addresses reclaimed from other IP address pools

when said high watermark exceeds said high watermark limit and when the

5 number of unallocated IP addresses is insufficient;

allocating an IP addresses from unallocated IP addresses when said high watermark

exceeds said high watermark limit and when the number of unallocated IP

addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from a local IP

10 address pool when said high watermark is less than said high watermark limit

and said low watermark is greater than said low watermark limit.

37. The program storage device of claim 33 wherein

each said local IP address pool further comprises a low watermark that indicates the

15 minimum number of IP addresses used by said network edge device;

said determining further comprises ascertaining whether said low watermark of said

address pool exceeds a low watermark limit; and

said method further comprises indicating one or more IP address pools should be

reallocated to reclaim IP addresses from the network element associated with

20 said low watermark when said low watermark exceeds said low watermark limit.

38. The program storage device of claim 35 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

said high watermark is expressed as a percentage of allocated IP addresses.

09765981-044904
T06T0-T0659200

39. The program storage device of claim 38 wherein said network operates according to a simple network management protocol (SNMP).

5

40. The program storage device of claim 39 wherein
said low watermark is stored in an expression MIB; and
said high watermark is stored in an expression MIB.

10 41. A program storage device readable by a machine, embodying a program of
instructions executable by the machine to perform a method to manage Internet
Protocol (IP) addresses on a data communications network, the method comprising:
receiving a communication;
allocating an available IP address from said local IP address pool if said
15 communication includes a connection request, said local IP address pool
associated with a different network edge device capable of accepting connection
requests;
determining whether said local IP address pool should be adjusted;
sending a alarm message to an IP pool manager when said IP address pool should be
20 adjusted; and
storing an IP address allocation when said communication includes an IP address
allocation.

FOOTNOTES

42. The program storage device of claim 41 wherein

said local IP address pool includes a high watermark that indicates the maximum
number of IP addresses used by said network edge device; and

5 said determining further comprises:

ascertaining whether said high watermark of a local address pool exceeds a high
watermark limit; and

indicating one or more IP address pools should be reallocated to give more IP
addresses to said network edge device when said high watermark exceeds
10 said high watermark limit.

43. The program storage device of claim 42 wherein

each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device; and

15 said determining further comprises:

ascertaining whether said low watermark of said address pool exceeds a low
watermark limit; and

said method further comprises indicating one or more IP address pools should be
reallocated to reclaim IP addresses from said network edge device when said
20 low watermark exceeds said low watermark limit.

FILED TO: TBSA 01-09-2000

44. The program storage device of claim 43 wherein said reallocating further comprises:

allocating an IP address from IP addresses reclaimed from other IP address pools

when said high watermark exceeds said high watermark limit and when the

5 number of unallocated IP addresses is insufficient;

allocating an IP addresses from unallocated IP addresses when said high watermark

exceeds said high watermark limit and when the number of unallocated IP

addresses is sufficient; and

reallocating one or more IP address pools to reclaim IP addresses from said local IP

10 address pool when said high watermark is less than said high watermark limit

and said low watermark is greater than said low watermark limit.

45. The program storage device of claim 41 wherein

each said local IP address pool further comprises a low watermark that indicates the

15 minimum number of IP addresses used by said network edge device; and

said determining further comprises:

ascertaining whether said low watermark of said local address pool exceeds a low

watermark limit; and

indicating one or more IP address pools should be reallocated to reclaim IP

20 addresses from the network element associated with said low watermark

when said low watermark exceeds said low watermark limit.

46. The program storage device of claim 43 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

0075991-01401
TOP SECRET

said high watermark is expressed as a percentage of allocated IP addresses.

47. The program storage device of claim 46 wherein said network operates according to a

5 simple network management protocol (SNMP).

48. The program storage device of claim 47 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

10

49. An apparatus for managing Internet Protocol (IP) addresses on a data

communications network, the apparatus comprising:

means for allocating a plurality of local IP address pools, each of said local IP address

pools associated with a different network edge device capable of accepting

15

connection requests requiring an IP address, said network edge device having a

local memory, said local memory including a local IP address pool database;

means for requesting IP address usage data from one or more of said network edge

devices;

means for receiving said requested IP address usage data;

20

means for determining whether one or more of said plurality of local IP address pools

should be reallocated based upon at least said requested IP address usage data;

means for reallocating one or more of said plurality of local IP address pools based

upon said determining; and

means for updating one or more of said local IP address pool databases and a global IP pool database based upon said reallocating, said global IP address pool database including the information maintained in each said local IP address pool.

5

50. The apparatus of claim 49 wherein

said local IP address pool includes a high watermark that indicates the maximum number of IP addresses used by said network edge device;

said means for determining further comprises means for ascertaining whether said

10

high watermark of a local address pool exceeds a high watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

should be reallocated to give more IP addresses to the network element

associated with said high watermark when said high watermark exceeds said high watermark limit.

15

51. The apparatus of claim 50 wherein

each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device;

said means for determining further comprises means for ascertaining whether said

20

low watermark of said address pool exceeds a low watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

should be reallocated to reclaim IP addresses from the network element

associated with said low watermark when said low watermark exceeds said low watermark limit.

TOP SECRET 041901

52. The apparatus of claim 51 wherein said reallocating further comprises:

means for allocating an IP address from IP addresses reclaimed from other IP address

5 pools when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is insufficient;

means for allocating an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

10 means for reallocating one or more IP address pools to reclaim IP addresses from a local IP address pool when said high watermark is less than said high watermark limit and said low watermark is greater than said low watermark limit.

53. The apparatus of claim 49 wherein

15 each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device;

said means for determining further comprises ascertaining whether said low watermark of said address pool exceeds a low watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

20 should be reallocated to reclaim IP addresses from the network element

associated with said low watermark when said low watermark exceeds said low watermark limit.

said low watermark is expressed as a percentage of allocated IP addresses; and

said high watermark is expressed as a percentage of allocated IP addresses.

5

55. The apparatus of claim 54 wherein said network operates according to a simple network management protocol (SNMP).

56. The apparatus of claim 55 wherein

10 said low watermark is stored in an expression MIB; and
 said high watermark is stored in an expression MIB.

57. An apparatus for managing Internet Protocol (IP) addresses on a data communications network, the apparatus comprising:

15 means for allocating a plurality of local IP address pools, each of said local IP address
pools associated with a different network edge device capable of accepting
connection requests requiring an IP address, said network edge device having a
local memory, said local memory including a local IP address pool database;
means for receiving a communication from said network edge device, said
20 communication including an IP address usage summary;
means for determining whether one or more of said plurality of local IP address pools
should be adjusted based upon said IP address usage summary; and
means for adjusting one or more of said plurality of local IP address pools based upon
said determining.

58. The apparatus of claim 57 wherein:

said local IP address pool includes a high watermark that indicates the maximum

5 number of IP addresses used by said network edge device;

said means for determining further comprises means for ascertaining whether said

high watermark of a local address pool exceeds a high watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

should be reallocated to give more IP addresses to the network element

10 associated with said high watermark when said high watermark exceeds said high watermark limit.

59. The apparatus of claim 10 wherein

each said local IP address pool further comprises a low watermark that indicates the

15 minimum number of IP addresses used by said network edge device;

said means for determining further comprises means for ascertaining whether said

low watermark of a said address pool exceeds a low watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

should be reallocated to reclaim IP addresses from the network element

20 associated with said low watermark when said low watermark exceeds said low watermark limit.

09766981-011901
TOP TO: T859260

60. The apparatus of claim 11 wherein said reallocating further comprises:

means for allocating an IP address from IP addresses reclaimed from other IP address

pools when said high watermark exceeds said high watermark limit and when the

number of unallocated IP addresses is insufficient;

means for allocating an IP addresses from unallocated IP addresses when said high

watermark exceeds said high watermark limit and when the number of

unallocated IP addresses is sufficient; and

means for reallocating one or more IP address pools to reclaim IP addresses from a

local IP address pool when said high watermark is less than said high watermark

limit and said low watermark is greater than said low watermark limit.

61. The apparatus of claim 57 wherein

each said local IP address pool further comprises a low watermark that indicates the

minimum number of IP addresses used by said network edge device;

said means for determining further comprises means for ascertaining whether said

low watermark of said address pool exceeds a low watermark limit; and

said apparatus further comprises means for indicating one or more IP address pools

should be reallocated to reclaim IP addresses from the network element

associated with said low watermark when said low watermark exceeds said low

watermark limit.

62. The apparatus of claim 59 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

00765991-011904
"T07T0" T059200

said high watermark is expressed as a percentage of allocated IP addresses.

63. The apparatus of claim 62 wherein said network operates according to a simple

5 network management protocol (SNMP).

64. The apparatus of claim 63 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

10

65. An apparatus for managing Internet Protocol (IP) addresses on a data

communications network, the apparatus comprising:

means for receiving a communication;

means for allocating an available IP address from a local IP address pool if said

15

communication includes a connection request, said local IP address pool

associated with a different network edge device capable of accepting connection

requests;

means for determining whether said local IP address pool should be adjusted;

means for sending a alarm message to a global IP pool manager when said IP address

20

pool should be adjusted; and

means for storing an IP address allocation when said communication includes an IP

address allocation.

0076363014US

66. The apparatus of claim 65 wherein

said local IP address pool includes a high watermark that indicates the maximum
number of IP addresses used by said network edge device; and

5 said means for determining further comprises:

means for ascertaining whether said high watermark of a local address pool
exceeds a high watermark limit; and

means for indicating one or more IP address pools should be reallocated to give
more IP addresses to said network edge device when said high watermark
10 exceeds said high watermark limit.

67. The apparatus of claim 66 wherein

each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device; and

15 said means for determining further comprises:

means for ascertaining whether said low watermark of said address pool exceeds a
low watermark limit; and

said apparatus further comprises means for indicating one or more IP address
pools should be reallocated to reclaim IP addresses from said network edge
20 device when said low watermark exceeds said low watermark limit.

68. The apparatus of claim 67 wherein said reallocating further comprises:

means for allocating an IP address from IP addresses reclaimed from other IP address

pools when said high watermark exceeds said high watermark limit and when the

number of unallocated IP addresses is insufficient;

means for allocating an IP addresses from unallocated IP addresses when said high

watermark exceeds said high watermark limit and when the number of

unallocated IP addresses is sufficient; and

means for reallocating one or more IP address pools to reclaim IP addresses from said

local IP address pool when said high watermark is less than said high watermark

limit and said low watermark is greater than said low watermark limit.

69. The apparatus of claim 65 wherein

each said local IP address pool further comprises a low watermark that indicates the

minimum number of IP addresses used by said network edge device; and

said means for determining further comprises:

means for ascertaining whether said low watermark of said local address pool

exceeds a low watermark limit; and

means for indicating one or more IP address pools should be reallocated to

reclaim IP addresses from the network element associated with said low

watermark when said low watermark exceeds said low watermark limit.

70. The apparatus of claim 67 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and

said high watermark is expressed as a percentage of allocated IP addresses.

71. The apparatus of claim 70 wherein said network operates according to a simple

5 network management protocol (SNMP).

72. The apparatus of claim 71 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

10

73. An apparatus capable of managing Internet Protocol (IP) addresses on a data communications network, said apparatus comprising:

a memory for storing a global IP address pool; and

a global IP pool manager, comprising:

15 an allocator capable of allocating a plurality of local IP address pools, each of said

local IP address pools associated with a different network edge device

capable of accepting connection requests requiring an IP address;

a requestor capable of requesting IP address usage data from one or more of said

network edge devices;

20 a determiner capable of determining whether one or more of said plurality of local

IP address pools should be reallocated based upon at least said requested IP

address usage data;

a reallocator capable of reallocating one or more of said plurality of local IP

address pools based upon said an indication from said determiner; and

09765991-04004
T06T0T0659260

databases and said global IP pool database based upon said reallocating.

number of IP addresses used by said network edge device; and

local address pool exceeds a high watermark limit and to indicate IP address pool

associated with said high watermark when said high watermark exceeds said high watermark limit.

minimum number of IP addresses used by said network edge device; and

address pool exceeds a low watermark limit and to indicate one or more IP

element associated with said low watermark when said low watermark exceeds

said low watermark limit.

allocate an IP address from IP addresses reclaimed from other IP address pools when

5 unallocated IP addresses is insufficient;

exceeds said high watermark limit and when the number of unallocated IP

reallocate one or more IP address pools to reclaim IP addresses from a local IP

10

$\begin{array}{c} \text{CH}_3 \\ | \\ \text{H}_2\text{C}-\text{O}-\text{CO}-\text{N}(\text{CH}_3)_2 \\ | \\ \text{H}_2\text{C}-\text{O}-\text{CO}-\text{N}(\text{CH}_3)_2 \\ | \\ \text{CH}_3 \end{array}$

each said local IP address pool further comprises a low watermark that indicates the

15

address pool exceeds a low watermark limit and to indicate one or more IP

element associated with said low watermark when said low watermark exceeds

20

said low watermark is expressed as a percentage of allocated IP addresses; and

said high watermark is expressed as a percentage of allocated IP addresses.

79. The apparatus of claim 78 wherein said network operates according to a simple network management protocol (SNMP).

5

80. The apparatus of claim 79 wherein
said low watermark is stored in an expression MIB; and
said high watermark is stored in an expression MIB.

10 81. An apparatus capable of managing Internet Protocol (IP) addresses on a data communications network, said apparatus comprising:
a memory for storing a global IP address pool; and
a global IP pool manager, comprising:
an allocator capable of allocating a plurality of local IP address pools, each of said
15 local IP address pools associated with a different network edge device
capable of accepting connection requests requiring an IP address;
a receiving interface capable of receiving a communication from said network
edge device, said communication including an IP address usage summary;
a determiner capable of determining whether one or more of said plurality of local
20 IP address pools should be reallocated based upon said IP address usage data;
a reallocator capable of reallocating one or more of said plurality of local IP
address pools based upon said an indication from said determiner; and
an updater capable of updating one or more of said local IP address pool
databases and said global IP pool database based upon said reallocating.

82. The apparatus of claim 81 wherein:

said local IP address pool includes a high watermark that indicates the maximum

5 number of IP addresses used by said network edge device; and

said determiner is further configured to ascertain whether said high watermark of a

local address pool exceeds a high watermark limit and to indicate one or more IP

address pools should be reallocated to give more IP addresses to the network

element associated with said high watermark when said high watermark exceeds

10 said high watermark limit.

83. The apparatus of claim 82 wherein

each said local IP address pool further comprises a low watermark that indicates the

minimum number of IP addresses used by said network edge device; and

15 said determiner is further configured to ascertain whether said low watermark of a

said address pool exceeds a low watermark limit and to indicate one or more IP

address pools should be reallocated to reclaim IP addresses from the network

element associated with said low watermark when said low watermark exceeds

said low watermark limit.

20

84. The apparatus of claim 83 wherein said reallocator is further configured to:

allocate an IP address from IP addresses reclaimed from other IP address pools when

said high watermark exceeds said high watermark limit and when the number of

unallocated IP addresses is insufficient;

allocate an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

- 5 reallocate one or more IP address pools to reclaim IP addresses from a local IP address pool when said high watermark is less than said high watermark limit and said low watermark is greater than said low watermark limit.

85. The apparatus of claim 81 wherein

- 10 each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device; and said determiner is further configured to ascertain whether said low watermark of said address pool exceeds a low watermark limit and to indicate one or more IP address pools should be reallocated to reclaim IP addresses from the network element associated with said low watermark when said low watermark exceeds
15 said low watermark limit.

86. The apparatus of claim 83 wherein

- said low watermark is expressed as a percentage of allocated IP addresses; and
20 said high watermark is expressed as a percentage of allocated IP addresses.

87. The apparatus of claim 86 wherein said network operates according to a simple network management protocol (SNMP).

88. The apparatus of claim 84 wherein

said low watermark is stored in an expression MIB; and

said high watermark is stored in an expression MIB.

5

89. An apparatus capable of managing Internet Protocol (IP) addresses on a data

communications network, said apparatus comprising:

a receiver capable of receiving a communication;

an allocator capable of allocating an available IP address from a local IP address pool

10

if said communication includes a connection request, said local IP address pool

associated with a different network edge device capable of accepting connection

requests;

a determiner capable of determining whether said local IP address pool should be

adjusted;

15

an notifier capable of sending a alarm message to a global IP pool manager when said

IP address pool should be adjusted; and

a memory capable of storing an IP address allocation when said communication

includes an IP address allocation.

20

90. The apparatus of claim 89 wherein

said local IP address pool includes a high watermark that indicates the maximum

number of IP addresses used by said network edge device; and

said determiner is further configured to ascertain whether said high watermark of a

local address pool exceeds a high watermark limit and to indicate one or more IP

Downloaded from

address pools should be reallocated to give more IP addresses to said network edge device when said high watermark exceeds said high watermark limit.

5 91. The apparatus of claim 90 wherein

each said local IP address pool further comprises a low watermark that indicates the minimum number of IP addresses used by said network edge device; and said determiner is further configured to ascertain whether said low watermark of said address pool exceeds a low watermark limit and to indicate one or more IP

10 address pools should be reallocated to reclaim IP addresses from said network edge device when said low watermark exceeds said low watermark limit.

92. The apparatus of claim 91 wherein said reallocator is further configured to:

allocate an IP address from IP addresses reclaimed from other IP address pools when
15 said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is insufficient;

allocate an IP addresses from unallocated IP addresses when said high watermark exceeds said high watermark limit and when the number of unallocated IP addresses is sufficient; and

20 reallocate one or more IP address pools to reclaim IP addresses from said local IP address pool when said high watermark is less than said high watermark limit and said low watermark is greater than said low watermark limit.

0976991 01494
T05T0 T05T0

93. The apparatus of claim 89 wherein

each said local IP address pool further comprises a low watermark that indicates the
minimum number of IP addresses used by said network edge device; and

5 said determiner is further configured to ascertain whether said low watermark of said
local address pool exceeds a low watermark limit and to indicate one or more IP
address pools should be reallocated to reclaim IP addresses from the network
element associated with said low watermark when said low watermark exceeds
said low watermark limit.

10

94. The apparatus of claim 91 wherein

said low watermark is expressed as a percentage of allocated IP addresses; and
said high watermark is expressed as a percentage of allocated IP addresses.

15

95. The apparatus of claim 94 wherein said network operates according to a simple
network management protocol (SNMP).

96. The apparatus of claim 95 wherein

said low watermark is stored in an expression MIB; and

20

said high watermark is stored in an expression MIB.

FOR FILING